

## Multi-Conductor Boat Cable

- Underwriters Lab Inc., listed boat cable rated 600 Volts meets Department of Transportation and Coast Gaurd specifications for electrical systems
- For temperatures up to 221°F (105°C) dry and 167°F (75°C) wet
- Cable has electro-tinned, plated copper strands for greater corrosion protection
- Each conductor is insulated and jacketed with flame retardant PVC for internal wiring of electric and electronic systems



Triplex



Duplex



DC Duplex



### Triplex - 3 Conductor

Standard Colors: Black, white, and green; white outer jacket

Part Number	AWG	Spooled Length in Feet
BC103-100	10/3	100'
BC103	10/3	1000'
BC123-100	12/3	100'
BC123	12/3	1000'
BC143-100	14/3	100'
BC143	14/3	1000'
BC163-100	16/3	100'
BC163	16/3	1000'

### Duplex - 2 Conductor

Standard Colors: Black and white; white outer jacket

Part Number	AWG	Spooled Length in Feet
BC102-100	10/2	100'
BC102	10/2	1000'
BC122-100	12/2	100'
BC122	12/2	1000'
BC142-100	14/2	100'
BC142	14/2	1000'
BC162-100	16/2	100'
BC162	16/2	1000'

### DC Duplex - 2 Conductor

Standard Colors: Red and yellow; white outer jacket

Part Number	AWG	Spooled Length in Feet
BC102-100-DC	10/2	100'
BC102-DC	10/2	1000'
BC122-100-DC	12/2	100'
BC122-DC	12/2	1000'
BC142-100-DC	14/2	100'
BC142-DC	14/2	1000'
BC162-100-DC	16/2	100'
BC162-DC	16/2	1000'

## Marine and Battery Cable

- Soft annealed bare copper with an extruded, high dielectric Polyvinyl Chloride (PVC) insulation
- Meets or exceeds UL, ABYC and SAE standards
- Meets UL VW-1 and CSA FT1 flame test requirements
- Excellent oil, heat, acid, and moisture resistance
- Constructed with 30 gauge stranding for superior flexibility
- -13°F to 221°F (-25°C to 105°C) temperature rating



Part Number	Color	AWG*	MM <sup>2</sup>	Bare copper stranding	Nominal OD	Wall Thickness	UL Style
AUF-2-BLK-THHW	Black	2	33.61	665 x 30	.485	4/64	1232
AUF-1/0-BLK-THHW	Black	1/0	53.50	1064 x 30	.625	5/64	1232
AUF-2/0-RED-THHW	Red	2/0	67.40	1323 x 30	.650	5/64	1232
AUF-2/0-BLK-THHW	Black	2/0	67.40	1323 x 30	.650	5/64	1232
AUF-3/0-BLK-THHW	Black	3/0	85.00	1666 x 30	.710	5/64	1232
AUF-4/0-RED-THHW	Red	4/0	107.0	2107 x 30	.805	5/64	1232
AUF-4/0-BLK-THHW	Black	4/0	107.0	2107 x 30	.805	5/64	1232

\*Other wire gauges available