

## Flexo PET™ Expandable Braided Sleeving

**ORDER ONLINE**

**FLEXO PET (PT) Grade Braided Sleeving** is used in electronics, automotive, marine and industrial wire harnessing applications where cost efficient and durable bundling and protection are critical. The unique braided construction and wide expandability—up to 150%—allows quick and easy installation over large connectors and long runs. PT is braided from 10mm polyethylene terephthalate (PET) monofilament yarns, and is available in industry standard colors. The material has an operating temperature range of -75°C (-103°F) to 125°C (257°F), and is resistant to chemical degradation, UV radiation, cuts and abrasions.

### General Purpose Braided Sleeving

| Part Number        | Nominal Size | Expansion Min Range | Expansion Max Range | Spool Size | Available Colors                       |
|--------------------|--------------|---------------------|---------------------|------------|--|
| PET18- <b>BB</b>   | 1/8"         | 3/32"               | 1/4"                | 225'       | All 19 colors pictured below           |
| PET14- <b>BB</b>   | 1/4"         | 1/8"                | 7/16"               | 200'       | All 19 colors pictured below           |
| PET38- <b>BB</b>   | 3/8"         | 3/16"               | 5/8"                | 125'       | All 19 colors pictured below           |
| PET12- <b>BB</b>   | 1/2"         | 1/4"                | 3/4"                | 100'       | All 19 colors pictured below           |
| PET58- <b>BB</b>   | 5/8"         | 3/8"                | 1"                  | 100'       | Red, White, Black, Carbon, Green, Blue |
| PET34- <b>BB</b>   | 3/4"         | 1/2"                | 1 1/4"              | 75'        | All 19 colors pictured below           |
| PET1- <b>BB</b>    | 1"           | 5/8"                | 1 5/8"              | 65'        | Purple, Blue, Black, Green, Gray, Red  |
| PET114- <b>BB</b>  | 1 1/4"       | 3/4"                | 1 3/4"              | 50'        | All 19 colors pictured below           |
| PET112- <b>BB</b>  | 1 1/2"       | 1"                  | 2 1/2"              | 40'        | All 19 colors pictured below           |
| PET1134- <b>BB</b> | 1 3/4"       | 1 1/4"              | 2 3/4"              | 30'        | All 19 colors pictured below           |
| PET2- <b>BB</b>    | 2"           | 1 1/2"              | 3 1/2"              | 50'        | All 19 colors pictured below           |
| PET212- <b>BB</b>  | 2 1/2"       | 1 3/4"              | 4 1/2"              | 50'        | All 19 colors pictured below           |
| PET3- <b>BB</b>    | 3"           | 2 1/2"              | 4 3/4"              | 50'        | All 19 colors pictured below           |

**TO ORDER**, add desired color code (**BB**) to the part number. Example: PET18-**RD**

**Available Colors:**

|                       |                  |
|-----------------------|------------------|
| Neon Red <b>NR</b>    | Red <b>RD</b>    |
| Neon Pink <b>NP</b>   | Orange <b>OR</b> |
| Neon Yellow <b>NY</b> | Yellow <b>YL</b> |
| Neon Green <b>NG</b>  | Green <b>GN</b>  |
| Neon Blue <b>NB</b>   | Blue <b>BL</b>   |
| Beige <b>BE</b>       | Purple <b>PP</b> |
| Carbon <b>CB</b>      | Clear <b>CL</b>  |
| Nitrox <b>NX</b>      | Black <b>BK</b>  |
| Patriot <b>PT</b>     | White <b>WT</b>  |
|                       | Gray <b>GY</b>   |

 -75°C TO 125°C

Flexo PET's wide color selection is ideal for complex color coding solutions over long runs of wire or cable. When cut correctly with a hot knife, the sealed ends of PET allow for varied solutions to cable bundling and protection.





## Flexo PET™ Pro-Pak

ORDER ONLINE



### General Purpose Braided Sleeving

| Base Part Number     | Diameter | Length |
|----------------------|----------|--------|
| PET18- <u>BB</u> -BP | 1/8"     | 50'    |
| PET14- <u>BB</u> -BP | 1/4"     | 45'    |
| PET38- <u>BB</u> -BP | 3/8"     | 30'    |
| PET12- <u>BB</u> -BP | 1/2"     | 24'    |
| PET34- <u>BB</u> -BP | 3/4"     | 15'    |

TO ORDER, add desired color code (BB) to the part number.  
Example: PET18-YL-BP



|             |           |   |
|-------------|-----------|---|
| Black       | <u>BK</u> |    |
| Red         | <u>RD</u> |    |
| Carbon      | <u>CB</u> |    |
| Neon Blue   | <u>NB</u> |    |
| Neon Yellow | <u>NY</u> |    |
| Gray        | <u>GY</u> |    |
| Beige       | <u>BE</u> |    |
| Clear       | <u>CL</u> |    |
| White       | <u>WT</u> |    |
| Neon Pink   | <u>NP</u> |    |
| Neon Red    | <u>NR</u> |    |
| Orange      | <u>OR</u> |    |
| Yellow      | <u>YL</u> |    |
| Nitrox      | <u>NX</u> |   |
| Neon Green  | <u>NG</u> |  |
| Green       | <u>GN</u> |  |
| Blue        | <u>BL</u> |  |
| Purple      | <u>PP</u> |  |

## Flexo F6™ Wrappable Split Braided Tube

ORDER ONLINE

F6's unique split, semi-rigid braided construction makes it the ideal solution for situations where ease of installation is of primary importance. The lateral split allows the tube to open up to accommodate a wide variety of bundling requirements, and the semi-rigid braid configuration simply closes around the entire installation without the need for any additional fasteners. The 10 mm PET braid is lightweight, quiet and flexible. The 25% edge overlap (at nominal diameter) allows coverage around inline plugs, connectors and splices. F6 will bend to a tight radius without distorting or splitting open. And, unlike full rigid tubing, will not impair or affect the flexibility of harnesses.

### Semi-Rigid Wrappable Split Braided Tube

| Part Number | Nominal Size | Package Quantity |
|-------------|--------------|------------------|
| FLEXO-18    | 1/8"         | 100'             |
| FLEXO-14    | 1/4"         | 100'             |
| FLEXO-38    | 3/8"         | 75'              |
| FLEXO-12    | 1/2"         | 75'              |
| FLEXO-34    | 3/4"         | 50'              |
| FLEXO-1     | 1"           | 50'              |
| FLEXO-112   | 1 1/2"       | 25'              |
| FLEXO-2     | 2"           | 25'              |

Available in Black only.



Bulk quantities available

### Nominal Diameter

The large 25% edge overlap allows easy installation over splices and inline connectors without exposing wires and cables.



EZ Carry - EZ Feed Dispenser Box Packaging