

Nylon and Polyethylene Convuluted Split Loom



NYLON: -40°F TO 230°F

POLYETHYLENE: -40°F TO 122°F

Split Loom Install Tool makes installation easy. Gather the wires into the bottom of the tool and insert into the split loom. Then slide the tool and wires through the tubing.

Loom Tool

Part Number	Fits Loom Diameter
SLT-025	1" – 1 1/4"
SLT-15	1/2" – 5/8"
SLT-20	3/4" – 7/8"
SLT-08	1/4" – 3/8"



Nylon Split Loom

Minimum order of 10 feet

Spool Part Number	Size	Length	Inside Diameter	Outside Diameter	Wall Thickness
LOOM14-SPOOL	1/4"	250 ft	.236" - .264"	.376" - .400"	.0047" - .0193"
LOOM38-SPOOL	3/8"	250 ft	.337" - .632"	.491" - .516"	.0059" - .0217"
LOOM12-SPOOL	1/2"	250 ft	.484" - .509"	.670" - .695"	.0071" - .0228"
LOOM58-SPOOL	5/8"	100 ft	.605" - .630"	.790" - .836"	.0083" - .0240"
LOOM34-SPOOL	3/4"	100 ft	.730" - .755"	.960" - .985"	.0094" - .0252"
LOOM1-SPOOL	1"	50 ft	1.000" - 1.039"	1.278" - 1.306"	.0118" - .0276"
Box Part Number	Size	Length	Inside Diameter	Outside Diameter	Wall Thickness
LOOM14-BOX	1/4"	10,000 ft	.236" - .264"	.376" - .400"	.0047" - .0193"
LOOM38-BOX	3/8"	5000 ft	.337" - .632"	.491" - .516"	.0059" - .0217"
LOOM12-BOX	1/2"	4000 ft	.484" - .509"	.670" - .695"	.0071" - .0228"
LOOM58-BOX	5/8"	2500 ft	.605" - .630"	.790" - .836"	.0083" - .0240"
LOOM34-BOX	3/4"	2000 ft	.730" - .755"	.960" - .985"	.0094" - .0252"
LOOM1-BOX	1"	300 ft	1.00" - 1.039"	1.278" - 1.306"	.0118" - .0276"
LOOM114-BOX	1 1/4"	250 ft	1.25" - 1.276"	1.437" - 1.484"	.0118" - .0276"
LOOM112-BOX	1 1/2"	150 ft	1.50" - 1.528"	1.858" - 1.925"	.0118" - .0276"
LOOM2-BOX	2"	100 ft	1.980" - 2.035"	2.343" - 2.409"	.0118" - .0276"

Polyethylene Split Loom

Minimum order of 10 feet

Spool Part Number	Size	Length	Inside Diameter	Outside Diameter	Wall Thickness
LOOM14PE-SPOOL	1/4"	250 ft	.236" - .264"	.376" - .400"	.0047" - .0193"
LOOM38PE-SPOOL	3/8"	250 ft	.337" - .632"	.491" - .516"	.0059" - .0217"
LOOM12PE-SPOOL	1/2"	250 ft	.484" - .509"	.670" - .695"	.0071" - .0228"
LOOM58PE-SPOOL	5/8"	100 ft	.605" - .630"	.790" - .836"	.0083" - .0240"
LOOM34PE-SPOOL	3/4"	100 ft	.730" - .755"	.960" - .985"	.0094" - .0252"
LOOM1PE-SPOOL	1"	50 ft	1.000" - 1.039"	1.278" - 1.306"	.0118" - .0276"
Box Part Number	Size	Length	Inside Diameter	Outside Diameter	Wall Thickness
LOOM14PE-BOX	1/4"	10,000 ft	.236" - .264"	.376" - .400"	.0047" - .0193"
LOOM38PE-BOX	3/8"	5000 ft	.337" - .632"	.491" - .516"	.0059" - .0217"
LOOM12PE-BOX	1/2"	4000 ft	.484" - .509"	.670" - .695"	.0071" - .0228"
LOOM58PE-BOX	5/8"	2500 ft	.605" - .630"	.790" - .836"	.0083" - .0240"
LOOM34PE-BOX	3/4"	2000 ft	.730" - .755"	.960" - .985"	.0094" - .0252"
LOOM1PE-BOX	1"	300 ft	1.00" - 1.039"	1.278" - 1.306"	.0118" - .0276"
LOOM114PE-BOX	1 1/4"	250 ft	1.25" - 1.276"	1.437" - 1.484"	.0118" - .0276"
LOOM112PE-BOX	1 1/2"	150 ft	1.50" - 1.528"	1.858" - 1.925"	.0118" - .0276"
LOOM2PE-BOX	2"	100 ft	1.980" - 2.035"	2.343" - 2.409"	.0118" - .0276"

Additional Cable Tie Tension Tools Available

Panduit GTS-E Cable Tie Tool installs and trims miniature, intermediate, and standard cross section nylon ties from .070" (1.8mm) to .190" (4.8mm) wide

- Lightweight, ergonomic design speeds installation and reduces user fatigue
- Low handle force
- Flush tie cut-off eliminates sharp edges, improves safety
- Adjustable tension
- Impact resistant resin housing



Part Number
GTS-E

- Use with miniature, intermediate, and standard cross section nylon ties from 3/32" (2.3mm) to 11/32" (8.73mm) wide, and up to 1.6mm thick

- Adjustable tension
- Neatly fastens and cuts tie in one action
- Flush cut-off eliminates sharp edges on ties.
- Ergonomic handle and trigger
- Aluminum body



Part Number
CP-382